

Reference: 06PC99
Issue Number: 1
Issue Date: February 2005
Supersedes Issue: 0

PC99 ANTI-VANDAL COATING

PRODUCT DESCRIPTION

A non-oxidising, non-setting coating formulated using a selection of various petroleum derivatives and durable pigments. This product is recommended by various police forces as an anti-intruder coating and to act as a deterrent to burglars and vandals against entry into dangerous areas. PC99 has the benefits of a wide working temperature from -20°C up to 60°C. Can be applied to most surfaces, low odour and solvent free.

USES

For use on drain pipes, sills, tops of wall and fences, garage and porch roofs, flat roofs etc, trees (to discourage theft of eggs), electricity pylons to prevent access to dangerous areas, telegraph poles, lamp posts to prevent climbing.

TECHNICAL PROPERTIES

Colour	Black, Grey, Red
Finish	Slight sheen
Specific Gravity	0.99
Volume Solids	100%
Recommended Film Thickness	400-500µ WFT / 400-500µ DFT
Theoretical Spreading Rate	2-2.5 m ² /litre
Application Method	Brush
Flash Point	150°C
VOC	0 g/litre
Drying Times	THIS PRODUCT DOES NOT DRY

CERTIFICATION/APPROVALS

RECOMMENDED SYSTEMS One coat system.

SURFACE PREPARATION

Remove all oil, grease etc. by detergent washing and rinsing with clean fresh water. Wire brush to remove loose dirt, existing paint flakes and any rust or corrosion products. Ensure that the surface to be coated is dry.

PRODUCT APPLICATION

Mixing	Mix well before use.
Thinners	Do not thin. If the product appears too thick to apply, warm product up to reduce viscosity.
Brush	Apply to recommended film thickness.
Cleaner	Thinner No.3
Cleanup Considerations	All equipment should be cleaned immediately after use with Thinner No.3 It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited.
The user must observe local health, safety and environmental regulations when using this product.
Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

PACK SIZES

5 litre, 2.5 litre, 1 litre.

PACK WEIGHTS

5 litre : 4.95 kg. 2.5 litre : 2.475 kg. 1 litre : 0.99 kg.

STORAGE CONDITIONS

Store in a cool, dry shaded area. Shelf life 12 months.

LIMITATIONS

Do not apply this product if the relative humidity exceeds 90% or if the substrate is within 3°C of the dew point.
Do not use on surfaces likely to be used by bona fide persons. We recommend applying the product at least 2.3 m. (7 feet) above ground level.
Do not apply other surface coatings over PC99.
To remove this coating use scrapers and wash surface with Thinner No.3
It would be prudent to erect a 'Warning Notice'.

DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.